

COLORBOND RENTAL VAN

Dimensions	
Overall Length mm	4,200mm Or 4,500mm
Overall Width mm	2,300mm
Overall Height mm	2,410mm Body Height
Construction	
Main Rail / Chassis	100mm PFC Steel Channel
Cross Members	75x50mm Steel RHS
Floor (Option of)	(1) 3mm Steel Smooth or Chequer Plate floor. (2) 3mm Alloy Chequer Plate Floor. (3) Smooth Hyper Grip Ply Floor
Front Wall (Option of)	(1) Square Front - Suitable for Nose Cone. (2) Angled Front Section - Not suitable for Nose Cone
Framing	30mm x 30mm Square Hollow Section
Roof	1 piece aluminium roof skin over white 3mm ply
Side Walls	Colorbond sheeting in white profile with White internal Ply sheets.
Rear Frame	Rear frame prepared to suit rear doors or full seal tailgate loader
Rear Doors	25mm FRP rear barns doors with single camlocks with stainless steel T-Catch door holds.
Tie Rails	(3x) ERW steel rope tie downs along side walls, front walls, roof.
External Specification	
Extrusions	Polished aluminium extruded angles to all perimeter corners, Polished aluminium extruded bottom rail
Mudguards	Aluminium Guards with GTB Mudflaps
Electrical Specs	
Internal Lighting	1x LED Worklamp mounted on rear frame wired into chassis park lights with switch at roadside rear quarter panel.
ADR Lighting	All Compulsary Lights are Narva LED and ADR compliant
Tail Lights	OEM tail lights used unless specified otherwise.
Options	
Nose Cone	Nose Cone mounted to front external wall.
Tool Box (GTB)	800mm GTB Roto Moulded Tool Box Mounted to Kerbside
Tool Box (Other)	800mm Steel Tool Box Mounted to Kerbside, Stainless or Black Lid Optional
Tail Lights	Narva LED Tail Lights. Note* Confirmation from OEM if suitable is required prior to fitting.
Tailgates	Rear frame is prepared to suit Tuck Away, Column, or Full Seal tailgates.
Water Bottle & Soap Dispenser.	GTB rotomoulded 50L water bottle c/w soap dispenser.
Dock Buffers	Rubber Dock Buffers to rearframe

